

# C2 Ceiling Paint Flat

## QUICK REFERENCE

SKU L8150	COVERAGE 400-450 sq ft/gal	VOC <50g/L
DRY - TOUCH 1-2 Hours	DRY - RECOAT 4 Hours	FULL CURE 14 Days
SIZES AVAILABLE Gallon, 5 Gallon	TYPE Acrylic/Vinyl Blend	REFLECTANCE 0-5% @ 85°

## Product Description

C2 Ceiling Paint is formulated to easily create beautiful ceilings by reducing the tendency to spot drywall imperfections and an absolutely flat appearance. The result is an appealing surface with easy application and seamless touchup.

## Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Apply one coat L1800 Wallboard Primer to entire surface. Finish with one or two coats of C2 Ceiling Paint.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with L1800 Wallboard Primer. When painting over dark colors, best results are achieved by priming entire surface. Finish with one or two coats of C2 Ceiling Paint.

## Application Instructions

L8150 C2 Ceiling Paint may be applied by roller (no less than 3/8-inch nap), brush (synthetic) or spray.

Coverage: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters) Overspreading can result in hiding problems.

**Thinning: Do not thin.**

**Airless Spray: Use a 12 to 15 mil size tip.**

Cleanup: Clean brushes, rollers, pads, etc. with warm, soapy water immediately after completion of painting.

## Technical Specifications

SPECIFICATION	VALUE
% Solids	39.88%
Weight per Gallon	12.38 +/-2
Flash Point	

