

Exterior Latex Matte

QUICK REFERENCE

SKU C5100	COVERAGE 450 sq ft/gal	VOC <50g/L
DRY - TOUCH 30 Minutes	DRY - RECOAT 2-4 Hours	FULL CURE 14 Days
SIZES AVAILABLE Gallon	TYPE 100% Acrylic Resin	REFLECTANCE 2-7% @ 85°

Product Description

C5100 Exterior Latex Matte is a 100% Acrylic formulation designed to be applied to most exterior surfaces. C5100 is specifically formulated to provide outstanding covering power, tenacious adhesion, excellent weathering capabilities and color retention. C5100 is an excellent choice to renew siding.

Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Remove mildew using a bleach solution of 1 part bleach to 4 parts water. Patch holes and cracks, sand smooth and remove sanding dust.

New Wood: Spot prime all knots and sappy areas with A9100 Exterior Alkyd Primer. Allow primed areas to dry and sand until smooth. Apply one coat of C3000 Exterior Latex Primer to entire surface. If required, sand knots again and remove dust. Finish with one or two coats of C5100 Exterior Latex Matte. Note: For tannin containing woods, best results are achieved by priming with A9000 Exterior Alkyd Primer.

Painted Surfaces: Remove all loose or peeling paint. Dull glossy surfaces. Prime entire surface as required using C3000 Exterior Latex Primer. Finish with one or two coats of C5100 Exterior Latex Matte.

Galvanized Metal: Clean surface with a high solvency Thinner. Prime using C3000 Exterior Latex Primer. Finish with one or two coats of C5100 Exterior Latex Matte.

Aluminum/Vinyl Siding: Clean surface using a pressure washer. Finish with one or two coats of C5100 Exterior Latex Matte. Note: Never use dark colors on aluminum or vinyl siding.

Application Instructions

Stir thoroughly prior to applying with roller (no less than 3/8th inch), brush (synthetic), pad or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)

Thinning: Do not thin.

Airless Spray: Use a 12 to 15 mil size tip.

Cleanup: Clean painting equipment and spills immediately using warm soapy water.

Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C)

Technical Specifications

SPECIFICATION	VALUE
% Solids	40.00%
Weight per Gallon	11.61 +/- .25
Flash Point	

Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only. Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.

Date Generated: March 08, 2026

C2 Exterior Latex Eggshell

QUICK REFERENCE

SKU C5200	COVERAGE 450 sq ft/gal	VOC <50g/L
DRY - TOUCH 30 Minutes	DRY - RECOAT 2-4 Hours	FULL CURE 14 Days
SIZES AVAILABLE Quart, Gallon	TYPE 100% Acrylic Resin	REFLECTANCE 15-25% @ 85°

Product Description

C5200 Exterior Latex Eggshell is a 100% Acrylic formulation designed for application to most exterior surfaces where a slight angular sheen is desired. C5200 is specifically formulated to provide outstanding covering power, excellent flow and leveling, tenacious adhesion and weathering characteristics (gloss and color retention) that are second to none.

Application Instructions

Stir thoroughly prior to applying with roller (no less than 3/8th inch), brush (synthetic), pad or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)

Thinning: Do not thin.

Airless Spray: Use a 12 to 15 mil size tip.

Cleanup: Clean painting equipment and spills immediately using warm soapy water.

Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C)

Technical Specifications

SPECIFICATION	VALUE
% Solids	40.00%
Weight per Gallon	11.30 +/- .25
Flash Point	

Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only. Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.

Date Generated: March 08, 2026

Exterior Latex Satin

QUICK REFERENCE

SKU C5300	COVERAGE 450 sq ft/gal	VOC <50g/L
DRY - TOUCH 30 Minutes	DRY - RECOAT 2-4 Hours	FULL CURE 14 Days
SIZES AVAILABLE Gallon	TYPE 100% Acrylic Resin	REFLECTANCE 15-25% @ 60°

Product Description

C5300 Exterior Direct to Substrate Latex Satin is a 100% Acrylic formulation designed to be applied to most exterior surfaces without a primer. The C5300 series is specifically formulated to provide outstanding covering power, tenacious adhesion, excellent stain resistance, superior weathering capabilities and great color retention. The C5300 series is a great choice for both aluminum and vinyl siding.

Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Remove mildew using a bleach solution of 1 part bleach to 4 parts water. (Wear protective eyewear, clothing and rubber gloves when treating mildew) Patch holes and cracks, sand and remove sanding dust.

New Wood: Spot prime all knots and sappy areas with A9100 Exterior Alkyd Primer. Allow primed areas to dry and sand until smooth. If required, prime and sand knots again and remove dust. Finish with two coats of C5300 tinted to your desired color. Note: For tannin containing woods such as Redwood and Cedar apply one coat of C5300 and let dry overnight. Apply a second coat the next day. Try a test area first as severely staining wood may require A9100 Exterior Alkyd Primer to block the stain.

Previously Painted Surfaces: Remove all loose or peeling paint. Dull glossy surfaces by scuff sanding. "Prime" any bare spots with C5300 and then finish with one or two coats of C5300 tinted to your desired color.

Galvanized Metal: Clean surface with a high solvency thinner. Wipe clean and dry then finish with one or two coats of C5300.

Aluminum/Vinyl Siding: Make certain that all chalk is removed from surface by cleaning with a pressure washer or mechanical device if required. Finish with one but preferably two coats of C5300. Note: Do not use dark colors on siding.

Masonry Surfaces: New masonry must be fully cured (90 days). Clean the surfaces with a pressure washer and apply two coats of C5300. For previously painted masonry, pressure wash and apply one or two coats.

Application Instructions

Stir thoroughly prior to applying with roller (no less than 3/8th inch), brush (synthetic), pad or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)

Thinning: Do not thin.

Airless Spray: Use a 12 to 15 mil size tip.

Cleanup: Clean painting equipment and spills immediately using warm soapy water.

Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C)

Technical Specifications

SPECIFICATION	VALUE
% Solids	40%
Weight per Gallon	11.00 +/- .2
Flash Point	

Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only. Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.

Date Generated: March 08, 2026

C Exterior Latex Semi-Gloss

QUICK REFERENCE

SKU C5400	COVERAGE 450 sq ft/gal	VOC <50g/L
DRY - TOUCH 30 Minutes	DRY - RECOAT 2-4 Hours	FULL CURE 14 Days
SIZES AVAILABLE Gallon	TYPE 100% Acrylic Resin	REFLECTANCE 45-65% @ 60°

Product Description

C5400 Exterior Latex Semi-Gloss is a 100% Acrylic formulation designed for application to most exterior surfaces where a semi-gloss finish is desired. C5400 is specifically formulated to provide outstanding covering power, exceptional flow and leveling, tenacious adhesion and weathering characteristics (gloss and color retention) that are second to none.

Application Instructions

Stir thoroughly prior to applying with roller (no less than 3/8th inch), brush (synthetic), pad or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)

Thinning: Do not thin.

Airless Spray: Use a 12 to 15 mil size tip.

Cleanup: Clean painting equipment and spills immediately using warm soapy water.

Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C)

Technical Specifications

SPECIFICATION	VALUE
% Solids	40.00%
Weight per Gallon	11.30 +/-2
Flash Point	

Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only. Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. See your C2 dealer for disposal recommendations in your area.

Date Generated: March 08, 2026