

## QUICK REFERENCE

SKU C2000	COVERAGE 400-450 sq ft/gal	VOC <50g/L
DRY - TOUCH 30 Minutes	DRY - RECOAT 2-4 Hours	FULL CURE 14 Days
SIZES AVAILABLE Quart, Gallon, 5 Gallon	TYPE Acrylic/Vinyl Blend	REFLECTANCE <2.5% @ 60°

## Product Description

C2000 C2 Studio Interior Latex Flat is an acrylic fortified low odor, scrubable finish for application in most residential or commercial environments. C2000 is specifically formulated to provide maximum coverage, spatterless application and virtually invisible touch-up.

## Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints or patched area and then see your C2 dealer for the appropriate primer recommendation. Finish with one or two coats of C2 Studio Interior Latex Flat.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2 primer recommended by your C2 dealer and then finish with one or two coats of C2 Studio Interior Latex Flat.

New Wood: Sand entire surface and apply one coat primer recommended by your C2 dealer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C2 Studio Interior Latex Flat.

## Application Instructions

C2000 C2 Studio Interior Latex Flat, may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)

**Thinning: Do not thin.**

**Airless Spray: Use a 12 to 15 mil size tip.**

**Cleanup: Clean painting equipment and spills immediately using warm soapy water.**

Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

## Technical Specifications

---

SPECIFICATION	VALUE
% Solids	35.20%
Weight per Gallon	11.49 +/- .2
Flash Point	

---

Date Generated: March 08, 2026

## QUICK REFERENCE

SKU C2100	COVERAGE 400-450 sq ft/gal	VOC <50g/L
DRY - TOUCH 30 Minutes	DRY - RECOAT 2-4 Hours	FULL CURE 14 Days
SIZES AVAILABLE Quart, Gallon, 5 Gallon	TYPE Acrylic/Vinyl Blend	REFLECTANCE 2-7% @ 85°

## Product Description

C2100 Studio Interior Latex Matte is an acrylic fortified low odor, scrubbable finish with a low sheen for uniform application in most residential or commercial environments. C2100 is specifically formulated to provide maximum coverage, spatterless application and virtually invisible touch-up.

## Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints or patched area and then see your C2 dealer for the appropriate primer recommendation. Finish with one or two coats of C2 Studio Interior Latex Flat.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2 primer recommended by your C2 dealer and then finish with one or two coats of C2 Studio Interior Latex Flat.

New Wood: Sand entire surface and apply one coat primer recommended by your C2 dealer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C2 Studio Interior Latex Flat.

## Application Instructions

C2000 C2 Studio Interior Latex Flat, may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)

**Thinning: Do not thin.**

**Airless Spray: Use a 12 to 15 mil size tip.**

**Cleanup: Clean painting equipment and spills immediately using warm soapy water.**

Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

## Technical Specifications

---

SPECIFICATION	VALUE
% Solids	36.00%
Weight per Gallon	11.12 +/- .2
Flash Point	

Date Generated: March 08, 2026

## QUICK REFERENCE

SKU C2200	COVERAGE 400-450 sq ft/gal	VOC <50g/L
DRY - TOUCH 30 Minutes	DRY - RECOAT 2-4 Hours	FULL CURE 14 Days
SIZES AVAILABLE Gallon, 5 Gallon	TYPE Acrylic/Vinyl Blend	REFLECTANCE 13-23% @ 85°

## Product Description

C2200 C2 Studio Interior Latex Eggshell is an acrylic fortified low odor, scrubable finish for application in most residential or commercial environments. C2200 is specifically formulated to provide maximum coverage, spatterless application and virtually invisible touch-up.

## Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints or patched area and then see your C2 dealer for the appropriate primer recommendation. Finish with one or two coats of C2 Studio Interior Latex Flat.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2 primer recommended by your C2 dealer and then finish with one or two coats of C2 Studio Interior Latex Flat.

New Wood: Sand entire surface and apply one coat primer recommended by your C2 dealer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C2 Studio Interior Latex Flat.

## Application Instructions

C2000 C2 Studio Interior Latex Flat, may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)

**Thinning: Do not thin.**

**Airless Spray: Use a 12 to 15 mil size tip.**

**Cleanup: Clean painting equipment and spills immediately using warm soapy water.**

Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

## Technical Specifications

SPECIFICATION	VALUE
% Solids	37.16%
Weight per Gallon	11.05+/-2
Flash Point	

Date Generated: March 08, 2026

## QUICK REFERENCE

SKU C2300	COVERAGE 400-450 sq ft/gal	VOC <50g/L
DRY - TOUCH 30 Minutes	DRY - RECOAT 2-4 Hours	FULL CURE 14 Days
SIZES AVAILABLE Gallon, 5 Gallon	TYPE Acrylic/Vinyl Blend	REFLECTANCE 15-25% @ 60°

## Product Description

C2300 C2 Studio Interior Latex Satin is an acrylic fortified low odor, scrubable finish for application in most residential or commercial environments. Primarily designed as a trim finish, C2300 is specifically formulated to provide maximum coverage, spatterless application and great touch-up.

## Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints or patched area and then see your C2 dealer for the appropriate primer recommendation. Finish with one or two coats of C2 Studio Interior Latex Flat.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2 primer recommended by your C2 dealer and then finish with one or two coats of C2 Studio Interior Latex Flat.

New Wood: Sand entire surface and apply one coat primer recommended by your C2 dealer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C2 Studio Interior Latex Flat.

## Application Instructions

C2000 C2 Studio Interior Latex Flat, may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)

**Thinning: Do not thin.**

**Airless Spray: Use a 12 to 15 mil size tip.**

**Cleanup: Clean painting equipment and spills immediately using warm soapy water.**

Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

## Technical Specifications

---

SPECIFICATION	VALUE
% Solids	37.86%
Weight per Gallon	10.60 +/- .2
Flash Point	

Date Generated: March 08, 2026

# C2 Studio Semi-Gloss

## QUICK REFERENCE

SKU C2400	COVERAGE 400-450 sq ft/gal	VOC <50g/L
DRY - TOUCH 30 Minutes	DRY - RECOAT 2-4 Hours	FULL CURE 14 Days
SIZES AVAILABLE Gallon, 5 Gallon	TYPE Acrylic/Vinyl Blend	REFLECTANCE 45-60% @ 60°

## Product Description

C2400 C2 Studio Interior Semi-gloss is an acrylic fortified low odor, scrubable finish for application in most residential or commercial environments. Primarily designed as a trim finish, C2400 is specifically formulated to provide maximum coverage, spatterless application and great touch-up.

## Surface Preparation

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas. Spot prime tape joints or patched area and then see your C2 dealer for the appropriate primer recommendation. Finish with one or two coats of C2 Studio Interior Latex Flat.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with C2 primer recommended by your C2 dealer and then finish with one or two coats of C2 Studio Interior Latex Flat.

New Wood: Sand entire surface and apply one coat primer recommended by your C2 dealer. Allow primer to dry. Sand smooth entire surface. Apply one or two coats of C2 Studio Interior Latex Flat.

## Application Instructions

C2000 C2 Studio Interior Latex Flat, may be applied by roller (no less than 3/8 inch nap), brush (synthetic) or spray.

Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters)

**Thinning: Do not thin.**

**Airless Spray: Use a 12 to 15 mil size tip.**

**Cleanup: Clean painting equipment and spills immediately using warm soapy water.**

Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.

## Technical Specifications

SPECIFICATION	VALUE
% Solids	37.65%
Weight per Gallon	10.25 +/- .2
Flash Point	

Date Generated: March 08, 2026