C2 PAINT

Studio Flat

COVERAGE	VOC	REFLECTANCE	DRY TO TOUCH	DRY TO RECOAT	FULL CURE
400-450 sq ft/gal	<50 g/L	<2.5 @ 60°	30 Minutes	2-4 Hours	14 Days

Premium performance. Exceptional value. C2 Studio Flat delivers dependable coverage, smooth application, and a durable scrubbable finish for residential and commercial interiors. With excellent touch-up capability and beautiful color, it offers an affordable way to elevate everyday spaces.

SURFACE PREPARATION

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax, and rust. Patch holes and cracks, sand them smooth, remove sanding dust, and spot-prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand drywall tape joints and other repaired areas smooth. Apply one coat of C2 Wallboard Primer (L1800) to the entire surface. Finish with one or two coats of C2 Studio Flat.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand them smooth. Dull glossy surfaces. Spot-prime with C2 Premium All Purpose Acrylic Primer (C1000). When painting over dark colors, best results are achieved by priming the entire surface. Finish with one or two coats of C2 Studio Flat.

APPLICATION INSTRUCTIONS

Stir the product thoroughly. Intermix tinted containers to ensure color uniformity. Do not thin. Do not apply when the temperature of the product, air, or surface is below 50°F (10°C).

Using a brush or roller, apply the product in full, even coats. If applying by airless spray, tip sizes of 0.012 - 0.015 are recommended.

Cleanup: Clean painting equipment and spills immediately using warm, soapy water.

TECHNICAL DATA

SKU	C2000	WEIGHT PER GALLON	11.55 +/-.2
SIZES AVAILABLE	Quart, Gallon, 5 Gallon	VOLUME SOLIDS	35%
RESIN TYPE	Vinyl Acrylic Resin		

Application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product. Consult the Safety Data Sheet before use.

711 S. 3RD AVE. MARSHALLTOWN, IA 50158

C2 PAINT

Studio Matte

COVERAGE	VOC	REFLECTANCE	DRY TO TOUCH	DRY TO RECOAT	FULL CURE
400-450 sq ft/gal	<50 g/L	2-7 @ 85°	30 Minutes	2-4 Hours	14 Days

Premium performance. Exceptional value. C2 Studio Matte delivers dependable coverage, smooth application, and a durable scrubbable finish for residential and commercial interiors. With excellent touch-up capability and beautiful color, it offers an affordable way to elevate everyday spaces.

SURFACE PREPARATION

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax, and rust. Patch holes and cracks, sand them smooth, remove sanding dust, and spot-prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand drywall tape joints and other repaired areas smooth. Apply one coat of C2 Wallboard Primer (L1800) to the entire surface. Finish with one or two coats of C2 Studio Matte.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand them smooth. Dull glossy surfaces. Spot-prime with C2 Premium All Purpose Acrylic Primer (C1000). When painting over dark colors, best results are achieved by priming the entire surface. Finish with one or two coats of C2 Studio Matte.

APPLICATION INSTRUCTIONS

Stir the product thoroughly. Intermix tinted containers to ensure color uniformity. Do not thin. Do not apply when the temperature of the product, air, or surface is below 50°F (10°C).

Using a brush or roller, apply the product in full, even coats. If applying by airless spray, tip sizes of 0.012 - 0.015 are recommended.

Cleanup: Clean painting equipment and spills immediately using warm, soapy water.

TECHNICAL DATA

SKU	C2100	WEIGHT PER GALLON	11.12 +/-.2
SIZES AVAILABLE	Quart, Gallon, 5 Gallon	VOLUME SOLIDS	36%
RESIN TYPE	Vinyl Acrylic Resin		

Application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product. Consult the Safety Data Sheet before use.

711 S. 3RD AVE. MARSHALLTOWN, IA 50158

C2 PAINT

Studio Eggshell

COVERAGE	VOC	REFLECTANCE	DRY TO TOUCH	DRY TO RECOAT	FULL CURE
400-450 sq ft/gal	<50 g/L	13-23 @ 85°	30 Minutes	2-4 Hours	14 Days

Premium performance. Exceptional value. C2 Studio Eggshell delivers dependable coverage, smooth application, and a durable scrubbable finish for residential and commercial interiors. With excellent touch-up capability and beautiful color, it offers an affordable way to elevate everyday spaces.

SURFACE PREPARATION

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax, and rust. Patch holes and cracks, sand them smooth, remove sanding dust, and spot-prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand drywall tape joints and other repaired areas smooth. Apply one coat of C2 Wallboard Primer (L1800) to the entire surface. Finish with one or two coats of C2 Studio Eggshell.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand them smooth. Dull glossy surfaces. Spot-prime with C2 Premium All Purpose Acrylic Primer (C1000). When painting over dark colors, best results are achieved by priming the entire surface. Finish with one or two coats of C2 Studio Eggshell.

APPLICATION INSTRUCTIONS

Stir the product thoroughly. Intermix tinted containers to ensure color uniformity. Do not thin. Do not apply when the temperature of the product, air, or surface is below 50°F (10°C).

Using a brush or roller, apply the product in full, even coats. If applying by airless spray, tip sizes of 0.012 - 0.015 are recommended.

Cleanup: Clean painting equipment and spills immediately using warm, soapy water.

TECHNICAL DATA

SKU	C2200	WEIGHT PER GALLON	11.07 +/-.2
SIZES AVAILABLE	Gallon, 5 Gallon	VOLUME SOLIDS	37%
RESIN TYPE	Acrylic/Vinyl Blend		

Application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product. Consult the Safety Data Sheet before use.

711 S. 3RD AVE. MARSHALLTOWN, IA 50158

C2 PAINT

Studio Satin

COVERAGE	VOC	REFLECTANCE	DRY TO TOUCH	DRY TO RECOAT	FULL CURE
400-450 sq ft/gal	<50 g/L	15-25 @ 60°	30 Minutes	2-4 Hours	14 Days

Premium performance. Exceptional value. C2 Studio Satin delivers dependable coverage, smooth application, and a durable scrubbable finish for residential and commercial interiors. With excellent touch-up capability and beautiful color, it offers an affordable way to elevate everyday spaces.

SURFACE PREPARATION

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax, and rust. Patch holes and cracks, sand them smooth, remove sanding dust, and spot-prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand drywall tape joints and other repaired areas smooth. Apply one coat of C2 Wallboard Primer (L1800) to the entire surface. Finish with one or two coats of C2 Studio Satin.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand them smooth. Dull glossy surfaces. Spot-prime with C2 Premium All Purpose Acrylic Primer (C1000). When painting over dark colors, best results are achieved by priming the entire surface. Finish with one or two coats of C2 Studio Satin.

APPLICATION INSTRUCTIONS

Stir the product thoroughly. Intermix tinted containers to ensure color uniformity. Do not thin. Do not apply when the temperature of the product, air, or surface is below 50°F (10°C).

Using a brush or roller, apply the product in full, even coats. If applying by airless spray, tip sizes of 0.012 - 0.015 are recommended.

Cleanup: Clean painting equipment and spills immediately using warm, soapy water.

TECHNICAL DATA

SKU	C2300	WEIGHT PER GALLON	10.60 +/-.2
SIZES AVAILABLE	Gallon, 5 Gallon	VOLUME SOLIDS	38%
RESIN TYPE	Acrylic/Vinyl Blend		

Application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product. Consult the Safety Data Sheet before use.

711 S. 3RD AVE. MARSHALLTOWN, IA 50158

C2 PAINT

Studio Semi-Gloss

COVERAGE	VOC	REFLECTANCE	DRY TO TOUCH	DRY TO RECOAT	FULL CURE
400-450 sq ft/gal	<50 g/L	45-60 @ 60°	30 Minutes	2-4 Hours	14 Days

Premium performance. Exceptional value. C2 Studio Semi-Gloss delivers dependable coverage, smooth application, and a durable scrubbable finish for residential and commercial interiors. With excellent touch-up capability and beautiful color, it offers an affordable way to elevate everyday spaces.

SURFACE PREPARATION

Clean surface to remove contaminants such as dirt, dust, oil, grease, wax, and rust. Patch holes and cracks, sand them smooth, remove sanding dust, and spot-prime.

New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand drywall tape joints and other repaired areas smooth. Apply one coat of C2 Wallboard Primer (L1800) to the entire surface. Finish with one or two coats of C2 Studio Semi-Gloss.

Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand them smooth. Dull glossy surfaces. Spot-prime with C2 Premium All Purpose Acrylic Primer (C1000). When painting over dark colors, best results are achieved by priming the entire surface. Finish with one or two coats of C2 Studio Semi-Gloss.

APPLICATION INSTRUCTIONS

Stir the product thoroughly. Intermix tinted containers to ensure color uniformity. Do not thin. Do not apply when the temperature of the product, air, or surface is below 50°F (10°C).

Using a brush or roller, apply the product in full, even coats. If applying by airless spray, tip sizes of 0.012 - 0.015 are recommended.

Cleanup: Clean painting equipment and spills immediately using warm, soapy water.

TECHNICAL DATA

SKU	C2400	WEIGHT PER GALLON	10.25 +/-.2
SIZES AVAILABLE	Gallon, 5 Gallon	VOLUME SOLIDS	38%
RESIN TYPE	Acrylic/Vinyl Blend		

Application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product. Consult the Safety Data Sheet before use.

711 S. 3RD AVE. MARSHALLTOWN, IA 50158